

1200SU-M
Single-Use Pump
with Injected Molded
Pump Chamber

Single-Use
Solutions for
Biotech &
Pharmaceutical
Applications

Responding to the voice of the customer, **Quattroflow™**
1200SU Series Single-Use Quaternary
Diaphragm Pumps

are now available with plastic pump chambers engineered with injected molded polyethylene (PE). Designed to be a more cost-effective solution, these next generation pump chambers save you time and money, removing the need for extensive cleaning, sterilization and complex cleaning validation.



© 2018 QUATTROFLOW

QTF-10100-F-02

Features & Benefits:

- About one-third lower in price than solid design polypropylene pump chambers
- Assembled under controlled and clean conditions
- Connections: 3/4" TC, front connections
- Max. pressure: 4 bar at 20°C (58 psi at 68°F)
- Range of flow: 6 – 1200 L/hr (1.6 – 317 gph)
- Max. temperature: 50°C (122°F), not autoclavable
- Chamber diameter: 119 mm (4.69 inch)
- Gamma irradiation possible

For more information contact:

ALMATEC Maschinenbau GmbH
Hochstraße 150-152
47228 Duisburg, Germany
Tel: +49 (2065) 89205-0 • Fax: +49 (2065) 89205-40
info@almatec.de
quattroflow.com

Where Innovation Flows

